optical fault locator

FR₂

Description

The Wilcom FR2 Fiber Ranger Fault Locator is a rugged, lightweight, hand-held, easy-to-use optical fault locator for multimode and singlemode applications. Using OTDR (Optical Time Domain Reflectometer) technology, the FR2 is designed to pinpoint faults in optical cable, that can be over 20 kilometers away, with amazing accuracy. The FR2 operates at the industry standard wavelength of 1310nm, and can display the distance to the fault in meters or feet.

Useful applications for the FR2 include testing: Wide Area Networks (WANs), telecommunication spans of up to 20 kilometers, Fiber-to-the-Curb, installation and maintenance of multimode and singlemode fiber cabling, and Military systems. The FR2 is an excellent tool for locating faulty connectors, end-of-fiber, and breaks in multimode and singlemode fiber cable.

The FR2 has been designed with the user in mind with easy to use features. It has a large easy to read LCD display, and a single measure push-button for activating the unit's measure operation. The Index of Refraction (IOR) is user selectable with a single push-button. The FR2 will display the distance to an event (fault) in either feet or meters. The FR2 has the ability to detect up to seven multiple events with the push of a single button.



Specifications:

| pcomoations | |
|----------------------------------|--------------------------------------|
| | |
| Optical Connector | Single Port |
| Emitter Type | Laser |
| Emitter Classification | Class I (FDA 21 CFR and IEC 825) |
| Wavelength | 1310 nm |
| Fiber Type | Multimode and Singlemode |
| Index of Refraction | 1.40 to 1.69 |
| Accuracy | +/- 2 m |
| IOR Error | 0.001 IOR = 0.67 m/km |
| Minimum Distance Measured | 30m |
| Maximum Distance Measured | 20km |
| Minimum Detectable Signal (10km) | -49 dB |
| Number of Events Detected | 7 |
| Operating Temperature | -10 °C to +50 °C |
| Storage Temperature | -20 °C to +60 °C |
| Power | 4 AA size alkaline batteries |
| Battery Life | 13,000 operations |
| Dimensions (HWD) | 7.7 x 4.0 x 1.7" (195 x 100 x 45 mm) |
| Weight | 0.9 lbs. (440g) |
| Connector Options | ST, FC or SC |
| Warranty | 1 year |
| Accessories | soft case |
| Patent Number | US 6,381,011,B1 |

Ordering Information:

| Description | Part Number |
|---------------------|-------------|
| FR2 w/ ST connector | 30000202 |
| FR2 w/ FC connector | 30000201 |
| FR2 w/ SC connector | 30000203 |

